



5T Portable HVAC Unit on All-Terrain Cart Part # 9746



Key Features

FAST: With its top-mount gear rack; wide, large diameter, all-terrain solid rubber; and integrated push/lift handles; ZUMRO's 5T Portable HVAC Unit is designed to facilitate quick deployments

SIMPLE: ZUMRO's 5T Portable HVAC Unit features a custom-designed plenum box, "plug and play" power cord, and remote thermostatic control option, making the system extremely easy to connect and place into operation

INTEGRATED: Single, integrated unit offers 62,000 BTU/HR cooling, 60,000 BTU/HR heating (expandable) and dehumidification in one compact package

DURABLE: Our rugged 14-gauge, powder-coated steel frame combined with shock-absorbing materials and all-weather capability ensure this HVAC will perform in the harshest conditions

CAREFREE: ZUMRO's 25' remote "fast acting" thermostatic control features an intuitive user interface and is designed specifically to alleviate temperature swings, ensuring that even an untrained person can properly deploy and operate the 5T Portable HVAC Unit

VERSATILE: ZUMRO provides a 500-LBS capacity gear rack as standard on our 5T Portable HVAC, making it the most versatile HVAC platform available

System Includes:

- Integrated 30' power supply cord (heat pump only)
- Remote or Panel-mounted thermostat control
- Integrated 600-LBS capacity top-mount gear rack,
- Solid rubber all-terrain tires
- Swivel axle with integrated T-Handle
- Heavy duty PVC ducts 12"dia/14"dia x 10' L
- Hinged side-mount lift handles

Technical Specs

CONSTRUCTION:

Frame: 1"x2" and 1"x2" Powder-Coated 14-Gauge Steel
Casters: Solid Rubber All-Terrain Tires
Handles: Integrated, Ergonomic Push/Lift Handles (x4)
Gear Rack: 600-LBS Capacity, Integrated Top-Mount
Ducts: 12"/14"x10' HD PVC with Integrated Belt Buckle Closure
Thermostat: Optional remote Unit with 25' Cord and Carrying Case

Power Cord:

(Heat Pump): 30' UL-Rated 50A CS6365

PERFORMANCE:

Cooling Capacity: 62,000 BTU/HR
Heating Capacity (Heat Pump Only): 60,000 BTU/HR Air
Supply: 2,250 CFM @ 0.1 Wet Coil
Dehumidifying: 50% RH Max
Operating Temperature Range: -40 DEG F - 125 DEG F
Rating Ambient: 95 DEG F
Max Power Draw (Heat Pump): 8.2kW @ 34.1A
Max Power Draw (Resistance Heater): +10kW @ 43A

DIMENSIONS:

Unit Dimensions (LxWxH): 61" x 35.5" x 53.5"
Unit Weight: 650 LBS